



SC600 Series Electronic PPTC Resettable Fuse SC600-200SW0D 400V Maximum Voltage

Our Product Introduction

Basic Information

- Place of Origin: Shenzhen, Guangdong, China
- Brand Name: SOCAY
- Certification: REACH, RoHS, ISO
- Model Number: SC600-200SW0D
- Minimum Order Quantity: 500PCS
- Price: Negotiable
- Delivery Time: 5-8 work days



Product Specification

- Name: PPTC Resettable Fuse
- Package Type: Radial Lead
- Operation Current: 0.2A
- I Trip: 0.4A
- Maximum Voltage: 400V
- I Max: 3A
- P Dtyp.: 1.5W
- Maximum Time To Trip Current: 1.0A
- Maximum Time To Trip Time: 10.0Sec
- Resistance Min: 5.0Ω
- Resistance Max: 9.0Ω
- Resistance 1max: 14.0Ω
- Highlight: **PPTC Resettable Fuse 400V ,
Electronic PPTC Resettable Fuse,**



More Images



for more products please visit us on socaydiode.com

Product Description

SC600 Series PPTC Resettable Fuse SC600-200SW0D Fast Delivery Time

PPTC Resettable Fuse DATASHEET: [SC600-200SW0D_v98.1.pdf](#)

Electrical Parameters:

| Part Number | I_{hold} (A) | I_{trip} (A) | V_{max} (Vdc) | I_{max} (A) | P_{dtyp} (W) | Maximum Time To Trip | | Resistance | | |
|-------------------------|-------------------|-------------------|--------------------|------------------|-------------------|----------------------|-------------|---------------------------|---------------------------|----------------------------|
| Resettable Polymer PPTC | | | | | | Current (A) | Time (S) | R_{min} (Ω) | R_{max} (Ω) | $R1_{max}$ (Ω) |
| SC600-200SW0D | 0.20 | 0.40 | 400 | 3.0 | 1.5 | 1.0 | 10.0 | 5.0 | 9.0 | 14.0 |

I_{hold} = PPTC Resettable Fuse Hold current: maximum current at which the device will not trip at 25 still air.
 I_{trip} = PPTC Resettable Fuse Trip current: minimum current at which the device will always at 25 still air.
 V_{max} = Maximum voltage device can withstand without damage at rated current.
 I_{max} = Maximum fault current device can withstand without damage at rated voltage.
 T_{trip} = Maximum time to trip(s) at assigned current.
 P_{dtyp} = Typical power dissipation: typical amount of power dissipated by the device when in state air environment.
 R_{min} = PPTC Resettable Fuse Minimum device resistance at 25 prior to tripping.
 R_{max} = Maximum device resistance at 25 prior to tripping.
 $R1_{max}$ = Maximum resistance of device at 25 measured one hour after tripping.
 Caution: Operation beyond the specified rating may result in damage and possible arcing and flame.

PPTC Resettable Fuse Features:

- u RoHS Compliant and Halogen-Free
- u Radial leaded Devices
- u Cured, flame retardant epoxy polymer insulating material meets UL94V-0 requirements
- u PPTC Resettable Fuse Operation Current: 0.20A, Maximum Voltage: 400Vdc, Operating Temperature: -40 to +85

PPTC Resettable Fuse Applications:

- u USB hubs, ports and peripherals
- u Power ports
- u IEEE1394 ports
- u Motor protection
- u Computers and peripherals
- u General electronics

Temperature Derating Chart – I_{hold} (A):

| Ambient Operation Temperature | -40 | -20 | 0 | 23 | 30 | 40 | 50 | 60 | 70 | 85 |
|-------------------------------|------|------|------|------|-----|-----|-----|-----|-----|-----|
| Percentage Reduction | 145% | 130% | 120% | 100% | 95% | 88% | 80% | 71% | 66% | 56% |

Test Procedures and Requirement:

| Test | Test Conditions | Accept/Reject Criteria |
|-----------------|--|--------------------------------------|
| Resistance | In still air @25±2°C | $R_{min} \leq R \leq R_{max}$ |
| Hold Current | 60 min, at I_{hold} , In still air @25±2°C | No trip |
| Time to Trip | Specified current, V_{max} , @25±2°C | $T \leq \text{Maximum Time To Trip}$ |
| Trip Cycle Life | V_{max} , I_{max} , 100 cycles | No arcing or burning |
| Trip Endurance | V_{max} , 24 hours | No arcing or burning |

PPTC Resettable Fuse Physical Specifications:

| | |
|---------------------------|---|
| Lead Material | 0.03-1.85A Tin-plated Copper clad steel 2.50-5.00A Tin-plated Copper |
| Soldering Characteristics | Solder ability per MIL-STD-202, Method 208E |
| Insulating Material | Cured, flame retardant epoxy polymer meets UL 94V-0 requirements. |
| Device Labeling | Marked with 'SC', voltage, current rating |

PPTC Resettable Fuse Packaging Quantity:

| Part Number | Quantity (pcs/reel) |
|---------------|---------------------|
| SC600-200SW0D | 500 |



 **Shenzhen Socay Electronics Co., Ltd.**



+8618126201429



sylvia@socay.com



socaydiode.com

4/F, Block C, HeHengXing Science & Technology Park, 19 MinQing Road, LongHua District, Shenzhen City,
GuangDong Province, China